


Item no.: 788-515
 Product description: RELAY SOCKET WITH RELAY AND STATUS INDICATOR 2
 CHANGEOVER CONTACTS AC 115 V



Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

Product group	6 (Electronics)
Contact material	AgNi 90/10
Nominal input voltage (Un) (DC)	AC 115 V
Input voltage range	Un \pm 10 %
Current consumption at VN (20 °C)	8 mA
max. switching voltage	AC 250 V
max. make current (resistive) at 10 % ED	4 s (AC) 15 A
Max. continuous current	2 x 8 A
Max. switching power (resistive)	2 x AC 2000 VA
Max. switching power (resistive)	DC see load limiting value graph
Max. switching load with load / without load	6 min ⁻¹ / 1200 min ⁻¹
Operating power	0,75 VA
Pull-in time (typ)	7 ms
Drop-out time (typ)	0 ms
Bounce time (typ)	3 ms
Normal operating method	100 % ED
Dielectric strength contact / coil (kV)	5 kV
Dielectric strength open contact	1 kV
nominal voltage per VDE 0110 section 1/4.97, IEC 60 664-1	250 V / 4 kV / 3
Mechanical life	5 x 10 ⁶ switching operation

Degree of protection
Type of relay

IP 20
RT 2



Ambient operating temperature	-25 °C ... +50 °C
Storage temperature	-40 °C ... +70 °C
Standards	DIN VDE 0140 Teil 1, DIN EN 61140; DIN VDE 0160, EN 50178; Schutzklasse II
Cross section [mm ²]	0.34 - 2.5 mm ²
Cross section [AWG]	22 - 14 AWG
Connection method	CONTACT CAGE CLAMP® CONNECTION
Weight	46.029 g
Color	gray
Wiring type	Front-entry
No. of connection Points	8
Height	54 mm
Height	2.126 in
Width	15 mm
Width	0.591 in
Depth	86 mm
Depth	3.39 in
Strip length from	9 mm
Strip length to	10 mm
Strip length	0.37 in
Mounting	TS 35



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm ²]
788-515	GL	44 627 - 07 HH			
788-515	PRS	TE/1717/880590/08			
788-515	UL	E175199 Sec.6			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected