

Sunmoon Battery

ER34615M

Lithium Thionyl Chloride Battery [Spiral Type]
Li/SOCI2 3.6V



• Electrical Specification

Nominal Capacity[10mA~2V] **13Ah**

The discharge capacity of battery depends on the environment temperature and the terminated voltage of the battery.

Nominal Voltage **3.6V**

Maximum Continuous Current **2000mA**

Maximum Pulse Current **3000mA**

Under temperature of $23\pm 2^{\circ}\text{C}$, the battery starts to discharge with $20\mu\text{A}$ base current. The battery releases one pulse $3000\text{mA}/0.5$ secs every 2 minutes during its discharging and the battery voltage shall not be less than 2.7V. The voltage value depends on pulse characteristics, temperature and the usage of the batteries.

Weight **115g**

Operating Temperature **$-55^{\circ}\text{C} \sim +85^{\circ}\text{C}$**

• Advantages

- High energy density over 430wh/kg
- Open circuit voltage $\geq 3.65\text{V}$, and operating voltage ranging from 3.3~3.6V
- Wide operating temperature range: $-55^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- Long storage life reaching 10 years [under normal room temperature]
- This series batteries are suitable for high power continuous discharge and pulse discharge

• Main Applications

IoT

Sensor

R&D
Instrument

Automotive
Telematics

Military
Equipment

Utility Meters
AMR&AMI

Alarms and
Security
Systems

Storage
and
Tracking
Devices

**Customer Satisfaction is the Purpose We Always Adhere to,
Continuous Improvement is the Direction We Always Pursue!**


Sunmoon Battery

ER34615M


Lithium Thionyl Chloride Battery [Spiral Type]
Li/SOCI₂ 3.6V





Typical Discharge Profiles at +23±2°C



Restored Capacity Versus Current and Temperature [2.0V cut-off]



Voltage Plateau Versus Current and Temperature



Available Terminations

- S: Standard Termination
- T: Solder Tabs
- P: Axial Pins
- Customized terminations are available

Warning

- Do not expose the battery to open flame, inflammable and explosive articles.
- Do not recharge, short-circuit, disassemble, incinerate the battery or heat the battery to more than 100°C.
- Do not use the battery beyond the permitted temperature range.

Wuhan Sunmoon Battery Co., Ltd.

Tel: +86-27-84732116 84730089
Add: No.231, Xingsan Road, Hannan District, Wuhan, Hubei Province, China

Post: 430090
Web: www.sunmoonbat.com
Email: info@sunmoonbat.com