



◆ SPECIFICATION

Model NO.	LBM24CV100B	LBM24CV100A	LBM24CV130V	LBM24CV130S	LBM24CHT200V	LBM24CHT200S
Video Output Mode	CVI	CVI/CVBS	CVI/CVBS	CVI/CVBS	CVI/AHD/TVI/CVBS	CVI/AHD/TVI/CVBS

Camera

Image Sensor	OV9732	AR0141	OV9750	IMX225	OV2710	IMX322
DSP	HTC960	HTC960	HTC960	HTC960	HTC1080	HTC1080
Image Resolution	720P	720P/960H	960P/960H	960P/960H	1080P/960H	1080P/960H
Effective Pixels	1.0MP, 1280x720	1.0MP, 1280x720	1.3MP, 1280x960	1.3MP, 1280x960	2.1MP, 1920x1080	2.4MP, 1920x1080
TV System	PAL/NTSC					
Electronic Shutter	1/25s~1/50,000s , 1/30s~1/60,000s					
S/N Ratio	≥50dB					
Scanning System	Progressive Scan					

Lens

Focus Length	Board Lens 3.6mm/F2.0					
Focus Control	Fixed					
Lens Type	Fixed					
Pixels	2M Pixels					
Auto Iris Support	NO					

Night Vision

Infrared LED	14μ x 18PCS (Optional)					
Infrared Distance	20M					
IR Status	Under 10 Lux by CDS					
IR Power On	CDS Auto Control					

Camera Features

Day/Night	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W	Auto (ICR) / Color / B&W
OSD Menu Language	NO	NO	NO	NO	YES	YES
White Balance	Auto	Auto	Auto	Auto	Auto/Manual	Auto/Manual
Gain Control	Auto	Auto	Auto	Auto	Auto	Auto
Noise Reduction	2D NR	2D NR	2D NR	2D NR	2D NR	2D NR
Picture Adjustment	NO	NO	NO	NO	YES	YES
WDR	NO	NO	NO	NO	DWDR	DWDR
OSD Support	NO	NO	NO	NO	YES	YES
UTC	NO	NO	NO	NO	YES	YES

General

Housing	Plastic,IP66					
Bracket	YES, Anti-Cut Bracket					
Dual Voltage	NO					
IR Cut Filter	YES					
Heater	NO					
Operation Temperature	-10℃ ~ +50℃ RH95% Max					
Storage Temperature	-20℃ ~ +60℃ RH95% Max					
Power Source	DC12V±10%, 500mA					
Dimension	160.8(W) x 62(H) x 62(D)mm					
Weight	380g					