

PAN/TILT IR ANTI-VANDAL DOME CAMERA WITH MOTORIZED VF LENS

DAIPT-390AX4



Main Features:

- Preset speed of 12°/Sec (max)
- Preset accuracy up to 0.1°
- Preset position, cruise, pattern and auto scan
- OSD Menu
- IP66, IK10 protection.
- Optical zoom
- 2MP "4in1" + PAL/NTSC
- 10m IR SMD LED
- True Day/Night with ICR filter
- Noise reduction (3D-DNR)
- WB/AGC/BLC
- CoC Support

Camera Specification

		DAI-PTZ
		DAIPT-390AX4
Sensor		1/2.9" CMOS
Resolution	HD Analog	2MP (AHD / CVI / TVI - 1920x1080)
	Analog	700TVL
System		PAL/NTSC Selected by Presets
Optical Zoom		x4 (2.8-12mm)
Digital Zoom		No
Minimum Focus Distance		1.5M
Horizontal Angle of View		106°(Wide) to 51.8°(Tele) 51.5°(Wide) to 12.8°(Tele)
Sync System		Internal
Min. Illumination		0.01lux (0 Lux with IR On)
Day & Night		Auto/Day/Night (ICR)
S/N Ratio		>50dB
Focus		Auto/Manual
Auto Gain		Auto/Manual
WDR		No
White Balance		ATW/Manual/Outdoor/Indoor
BLC		On/Off
Shutter Speed		1/50~1/10000
Sense Up		No
Noise Reduction		3D-DNR
Stabilizer		No
Flip		On/Off
Iris		Auto
Flickerness		No



Pan/Tilt Specification

Pan tilt Range	250° Pan/ 65° Tilt
Pan tilt Speed	Max Preset Speed: 12°/Sec Manual: 0.5°~12°/Sec (Proportional to Zoom)
Preset	255
Pattern	No
Auto Scan	No
Group	No
Schedule	No
Privacy Zone Masking	No
Park Function	Yes (Preset 1 Only)

Communication Specification

Data Type	CoC* (Control over Coax)
Protocols	CoC
Baud Rates	2400
Camera ID	N/A
Alarm I/O	No
On Screen Display	OSD menu, Camera position

Mechanical

IR Distance	10m IR SMD LED
Fan / Heater	No
Sunshield	No
Humidity range	<90%
Power Supply	12VDC/1A (Not supplied)
Operation temperature	-20°C~+60°C
Dimensions	Ø110*90mm
Ingress Protection	IP66, IK10
Weight	400gr

*CoC must be supported on the controlling unit as well

*CoC not supported in CVBS mode