

# LM55-S400

## 55" UHD LED Monitor



### Features :

- 4K ultra-HD resolution
- Industrial level LCD panel, suitable for extensive 24/7 continuous works
- 4-side 8mm narrow bezel design
- High fidelity digital processing, brilliant and vivid video
- Built-in 3D COMB filter and 3D Noise Reduction
- 6ms response time, no image ghosting
- 1.07B color, display every details of video
- Using tamper-proof metal housing, stable and reliable
- Professional thermal design to extend equipment lifespan
- Built-in power, low energy consumption, ultra-quiet
- Abundant interfaces HDMI, DP, VGA, USB, Audio, RS232

### Technical Specification

#### Model

Model	LM55-S400
-------	-----------

#### System

Diagonal	55"(16:9)
Resolution	3840×2160 (UHD)
Backlight	LED
Brightness/Luminance (Standard)	450cd/m <sup>2</sup>
Contrast	5500:1
Angle of view	178°/178°(horizontal/vertical)
Response time	6(GTG) ms
Display Color	1.07B(10bit)
Life Time	30,000 hours
VESA	400×400mm

#### Signals

Input	DP 1.2a×1, HDMI 2.0×2, VGA(D-Sub)×1, USB multimedia×1, Audio×1, RJ45(RS232)×1	
Output	RJ45(RS232)×1	
	Speaker	5W×2

#### General

Consumption (Standard)	<170W
Consumption (Standby)	≤0.5W



Power Supply	AC100~240V (+/-10%), 50/60 Hz
Net Weight	25.2kg
Gross Weight	35kg
Dimensions(no base)	1227.2×699.6×65.0mm
Work Environment	Temperature: 0℃~40℃
	Humidity: 10%~85%

#### Accessory

Standard	HDMI cable, power cable, hanging bracket
Optional	Pedestal

Dimensions(mm)

