

400
VOLT

GATE OPERATOR **BIG** 18QI

For gates up to 2500 Kg

500BIG18QI

400 V three-phase sliding gate operator complete with electronic control unit. Maximum gate weight 2500 kg. STAINLESS STEEL housing.


See page 25 for accessories

Features:

- commercial use
- for gates up to 2500 kg
- 400 V three-phase gate operator
- STAINLESS STEEL housing
- manual release mechanism
- adjustable mechanical clutch


Pros:

- suitable for large sliding gates
- high torque and power thanks to the three-phase technology
- self-ventilated operator to increase the working cycle
- metal and bronze gears to increase endurance and reduce noise



Technical features

	BIG18QI
Power supply	400 V AC (50 - 60 Hz)
Motor power supply	400 V AC
Absorption	3 A
Power rating	1000 W
Speed maneuver	10 m/min
Duty cycle	55 %
Max. thrust	1850 N
Operating temperature	-20° C + +55° C
Motor thermal protection	150° C
Degree of protection	IP 54
Max. gate leaf weight	2500 kg
Pinion module	Module 4
Electronic control unit	D703



The above represented installation does not include safety devices such as safety edges. Their addition depends upon the risk assessment made on any installation in accordance with EN 12445-12453 standards.



OPERATOR BIG 30Q

**400
VOLT**

For gates up to 3500 Kg

500BIG30Q

400 V three-phase sliding gate operator complete with electronic control unit. Maximum gate weight 3500 kg.

See page 25 for accessories

Technical features

BIG30Q


Power supply	400 V AC (50 - 60 Hz)
Motor power supply	400 V AC
Absorption	3,6 A
Absorbed power	1500 W
Speed maneuver	12,5 m/min
Duty cycle	50 %
Max. thrust	3500 N
Operating temperature	-20° C ÷ +55° C
Motor thermal protection	150° C
Degree of protection	IP 54
Max. gate leaf weight	3500 kg
Pinion module	Module 4
Electronic control unit	D703

Features:


- commercial use
- for gates up to 3500 kg
- 400 V three-phase gate operator
- oil bath vertical pinion operator
- painted steel housing
- manual release mechanism
- mechanical clutch for crush prevention

Pros:

- suitable for large sliding gates
- high torque and power thanks to the three-phase technology
- self-ventilated operator to increase the working cycle
- metal and bronze gears to increase endurance and reduce noise



The above represented installation does not include safety devices such as safety edges. Their addition depends upon the risk assessment made on any installation in accordance with EN 12445-12453 standards.



400
VOLT

GATE OPERATOR

BIG 40Q

For gates up to 4000 Kg

500BIG40Q

400 V three-phase sliding gate operator for intensive use complete with electronic control unit and "soft-start". Maximum gate weight 4000 kg.

Features:

- commercial use
- for gates up to 4000 kg
- 400 V three-phase gate operator
- oil bath vertical pinion operator
- soft start acceleration ramp and soft stop
- manual release mechanism
- Module 6 rack pinion version available upon request
- mechanical clutch for crush prevention


Pros:

- suitable for huge sliding gates
- high torque and power thanks to the three-phase technology
- self-ventilated operator to increase the working cycle
- metal and bronze gears to increase endurance and reduce noise
- intensive use (50% duty cycle)



Technical features

	BIG40Q
Power supply	400 V AC (50 - 60 Hz)
Motor power supply	400 V AC
Absorption	3,6 A
Power rating	1500 W
Max. operating speed	12,5 m/min
Duty cycle	50 %
Max. thrust	3500 N
Operating temperature	-20° C + +55° C
Motor thermal protection	150° C
Degree of protection	IP 54
Max. gate leaf weight	4000 kg
Pinion module	Module 4
Electronic control unit	D703



The above represented installation does not include safety devices such as safety edges. Their addition depends upon the risk assessment made on any installation in accordance with EN 12445-12453 standards.



Accessories for "BIG" series of Sliding Gate Operators



400CP12
BIG18QI counterplate



S-600D703M00
230/400 V replacement
electronic control unit for
one gate operator with
electrical brake



400CP30
BIG30Q counterplate



400CFZ22
Steel rack 22x22 (Module 4,
max 3000 kg)



400CP40
BIG40Q counterplate



400VSF20
Screws and brackets for
400CFZ22 (40 units per
pkg)



900BSD15 **NEW**
Deformable safety edge kit
l=1,5 m



550CFZ06
Steel rack 30x30 (Module 6,
max 4000 kg)



900BSD20 **NEW**
Deformable safety edge kit
l=2 m



M-ING0000Z12BIG
Pinion module 6
(BIG30Q/40Q)



900TWC
Wireless safety edge
transmitter



C-TARG
Aluminium CE mark label,
self adhesive



900TWM
Wireless safety edge
master receiver



750COL
Control unit mounting post



700BAP4
Gate stopper with spring



250RXSM2 **NEW**
Self-learning, two-channel,
433,92 MHz plug-in radio
receiver. Accepts up to 14 rolling
code transmitters or unlimited
dipswitch transmitters.



C-CRT
Warning signal



250SM126 **NEW**
Memory card for 126 radio
codes



Further accessories:
Transmitters page 110
Photocells page 116
Flashing lights page 119