

Horn Strobes

SpectrAlert Advance® Horn Strobes

SpectrAlert Advance horn strobes are rich with features guaranteed to cut installation time and maximize profits. Intended for full building notification as well as on the property ground, they produce a loud sound to notify occupants to evacuate the buildings; the strobe is intended to notify those that may have a hearing impairment. Features include a universal mounting plate with a preliminary snap-in feature to hold the product in place for the screw attachment, 11 field-selectable candela settings, and rotary switches to select horn tone and volume settings. Compatible with 12- or 24-volt systems. SpectrAlert Advance horn strobes are listed to UL 1971 and UL 464 for public mode evacuation. Model numbers with a “K” suffix are outdoor products that are listed to UL 1638 and UL 464 for private mode evacuation. The outdoor products are rated from -40° F to 151° F (-40° C to 66° C) and have a NEMA 4X rating.



Ceiling-Mount Horn Strobes

Location	Red Model No.	White Model No.	Candela	Marking	Description
Indoor	PC2R	PC2W	Standard	FIRE	2-Wire, Clear Lens
	—	PC2W-SP	Standard	FUEGO	2-Wire, Clear Lens
	PC2RH	PC2WH	High	FIRE	2-Wire, Clear Lens
	PC4R	PC4W	Standard	FIRE	4-Wire, Clear Lens
	PC4RH	—	High	FIRE	4-Wire, Clear Lens
Outdoor	PC2RK	PC2WK	Standard	FIRE	2-Wire, Clear Lens
	PC2RHK	PC2WHK	High	FIRE	2-Wire, Clear Lens
	—	PC4WK	Standard	FIRE	2-Wire, Clear Lens



Wall-Mount Horn Strobes

Location	Red Model No.	White Model No.	Candela	Marking	Description
Indoor	P2R	P2W	Standard	FIRE	2-Wire, Clear Lens
	P2R-SP	—	Standard	FUEGO	2-Wire, Clear Lens
	P2RH	P2WH	High	FIRE	2-Wire, Clear Lens
	P4R	P4W	Standard	FIRE	4-Wire, Clear Lens
	P4RH	—	High	FIRE	4-Wire, Clear Lens
Outdoor	P2RK	P2WK	Standard	FIRE	2-Wire, Clear Lens
	P2RK-R	P2WK-R	Standard	FIRE	2-Wire, Clear Lens, Device Only
	P2RHK	P2WHK	High	FIRE	2-Wire, Clear Lens
	P2RHK-R	P2WHK-R	High	FIRE	2-Wire, Clear Lens, Device Only
	P2RHK-120	—	High	FIRE	2-Wire, Clear Lens, 120 V
	P4RK	P4WK	Standard	FIRE	4-Wire, Clear Lens
	P4RK-R	—	Standard	FIRE	4-Wire, Clear Lens, Device Only

Notes:

- Standard Candela settings: 15, 15/75, 30, 75, 95, 110, and 115
- High Candela settings: 135, 150, 177, and 185
- -SP denotes “FUEGO” printed housing.
- -R represents replacement device only, ships minus plastic weatherproof back box.
- -R outdoor replacement models are meant for use with WTP series of weatherproof flush-mount plates or SA-WBB outdoor metal weatherproof back boxes.