




## RG6 Tri-shield Coaxial Cable SPE

DATE:2019.04.22

Cross Section	Features																																																																																																																																																																																																						
	<ul style="list-style-type: none"> <li>• High-Grade RG6 Coaxial Cable</li> <li>• 18AWG Solid Copper-Clad Steel</li> <li>• Suitable for Digital HDTV Applications, CATV and Digital Satellite Installations</li> <li>• cETLus, CE、RoHS Compliant</li> <li>• 1000ft Wooden Spool</li> </ul>																																																																																																																																																																																																						
Performance																																																																																																																																																																																																							
Electrical Characteristics:[@68°F.(20°C.)]																																																																																																																																																																																																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #008080; color: white;"> <th colspan="2" style="text-align: center;">DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td colspan="2">RG6 Tri Shield, 18 AWG CCS, 60% Aluminum Braid, PVC Jacket, 1000ft Wooden Spool.</td> </tr> <tr style="background-color: #008080; color: white;"> <th colspan="2" style="text-align: center;">Technical Data</th> </tr> <tr> <td>Operating Temperature Range(°C)</td> <td style="text-align: center;">-20~75</td> </tr> <tr> <td>Reference Standard:</td> <td style="text-align: center;">cETLus、CE、RoHS</td> </tr> <tr style="background-color: #008080; color: white;"> <th colspan="2" style="text-align: center;">Construction</th> </tr> <tr> <td><b>Conductor</b></td> <td></td> </tr> <tr> <td>Size</td> <td style="text-align: center;">18AWG</td> </tr> <tr> <td>Material</td> <td style="text-align: center;">Copper Clad Ateel(CCS)</td> </tr> <tr> <td>Construction</td> <td style="text-align: center;">1.02±0.01mm</td> </tr> <tr> <td><b>Dielectric</b></td> <td></td> </tr> <tr> <td>Material</td> <td style="text-align: center;">Foam PE</td> </tr> <tr> <td>Diameter</td> <td style="text-align: center;">4.75±0.01mm</td> </tr> <tr> <td>Color</td> <td style="text-align: center;">White</td> </tr> <tr> <td><b>First Shield</b></td> <td style="text-align: center;">Bonded Aluminum Foil</td> </tr> <tr> <td><b>Braid</b></td> <td style="text-align: center;">Aluminum Wire(Alu-Mag )</td> </tr> <tr> <td>Coverage</td> <td style="text-align: center;">60%x16x6x0.12±0.005mm</td> </tr> <tr> <td><b>Third Shield</b></td> <td style="text-align: center;">Aluminum Foil</td> </tr> <tr> <td><b>Jacket</b></td> <td></td> </tr> <tr> <td>Material</td> <td style="text-align: center;">PVC</td> </tr> <tr> <td>Diameter</td> <td style="text-align: center;">7.0±0.01mm</td> </tr> <tr> <td>Color</td> <td style="text-align: center;">White</td> </tr> </tbody> </table>	DESCRIPTION		RG6 Tri Shield, 18 AWG CCS, 60% Aluminum Braid, PVC Jacket, 1000ft Wooden Spool.		Technical Data		Operating Temperature Range(°C)	-20~75	Reference Standard:	cETLus、CE、RoHS	Construction		<b>Conductor</b>		Size	18AWG	Material	Copper Clad Ateel(CCS)	Construction	1.02±0.01mm	<b>Dielectric</b>		Material	Foam PE	Diameter	4.75±0.01mm	Color	White	<b>First Shield</b>	Bonded Aluminum Foil	<b>Braid</b>	Aluminum Wire(Alu-Mag )	Coverage	60%x16x6x0.12±0.005mm	<b>Third Shield</b>	Aluminum Foil	<b>Jacket</b>		Material	PVC	Diameter	7.0±0.01mm	Color	White	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Frequency (MHZ)</th> <th style="width: 15%;">Attenuation Max(dB/100ft)</th> <th style="width: 15%;">Attenuation Max(dB/100m)</th> <th colspan="2" style="width: 55%;">SRL (dB)</th> </tr> </thead> <tbody> <tr> <td>5</td> <td style="text-align: center;">0.79</td> <td style="text-align: center;">2.57</td> <td rowspan="6" style="text-align: center; vertical-align: middle;">5~1000MHz</td> <td rowspan="6" style="text-align: center; vertical-align: middle;">&gt;=20</td> </tr> <tr> <td>10</td> <td style="text-align: center;">0.82</td> <td style="text-align: center;">2.66</td> </tr> <tr> <td>50</td> <td style="text-align: center;">1.47</td> <td style="text-align: center;">4.79</td> </tr> <tr> <td>100</td> <td style="text-align: center;">2.05</td> <td style="text-align: center;">6.72</td> </tr> <tr> <td>200</td> <td style="text-align: center;">2.84</td> <td style="text-align: center;">9.28</td> </tr> <tr> <td>400</td> <td style="text-align: center;">4.06</td> <td style="text-align: center;">13.28</td> </tr> <tr> <td>700</td> <td style="text-align: center;">5.6</td> <td style="text-align: center;">18.36</td> <td rowspan="6" style="text-align: center; vertical-align: middle;">1001~3000MHz</td> <td rowspan="6" style="text-align: center; vertical-align: middle;">&gt;=15</td> </tr> <tr> <td>900</td> <td style="text-align: center;">6.24</td> <td style="text-align: center;">20.43</td> </tr> <tr> <td>1000</td> <td style="text-align: center;">6.6</td> <td style="text-align: center;">21.61</td> </tr> <tr> <td>1200</td> <td style="text-align: center;">7.5</td> <td style="text-align: center;">24.59</td> </tr> <tr> <td>1450</td> <td style="text-align: center;">8.04</td> <td style="text-align: center;">26.36</td> </tr> <tr> <td>1800</td> <td style="text-align: center;">8.84</td> <td style="text-align: center;">28.98</td> </tr> <tr> <td>2200</td> <td style="text-align: center;">9.77</td> <td style="text-align: center;">32.03</td> <td></td> <td></td> </tr> <tr> <td>2500</td> <td style="text-align: center;">11.13</td> <td style="text-align: center;">36.47</td> <td></td> <td></td> </tr> <tr> <td>2750</td> <td style="text-align: center;">11.58</td> <td style="text-align: center;">37.94</td> <td></td> <td></td> </tr> <tr> <td>3000</td> <td style="text-align: center;">12.06</td> <td style="text-align: center;">39.54</td> <td></td> <td></td> </tr> <tr> <td colspan="3"></td> <td colspan="2">Dielectric Strength (kV/min)</td> <td style="text-align: center;">1</td> </tr> <tr> <td colspan="3"></td> <td colspan="2">Impedence (ohms)</td> <td style="text-align: center;">75±3.0</td> </tr> <tr> <td colspan="3"></td> <td colspan="2">Capacitance (pF/ft)</td> <td style="text-align: center;">16.53</td> </tr> <tr> <td colspan="3"></td> <td colspan="2">Conductor,DC@20 °C</td> <td style="text-align: center;">31</td> </tr> <tr> <td colspan="3"></td> <td colspan="2">DC Loop Resistance@ 20°C (ohms/kft)</td> <td style="text-align: center;">45.45</td> </tr> <tr> <td colspan="3"></td> <td colspan="2">Velocity Of Propagation (%)</td> <td style="text-align: center;">85</td> </tr> <tr style="background-color: #008080; color: white;"> <th colspan="5" style="text-align: center;">Mechanical Characteristics:</th> </tr> <tr> <td colspan="2">Test Object</td> <td colspan="2"></td> <td>Jacket</td> <td></td> </tr> <tr> <td colspan="2">Test Material</td> <td colspan="2"></td> <td>PVC</td> <td></td> </tr> <tr> <td>Before</td> <td>Tensile strength (Mpa)</td> <td colspan="2"></td> <td>13.8</td> <td></td> </tr> <tr> <td>Aging</td> <td>Elongation (%)</td> <td colspan="2"></td> <td>200</td> <td></td> </tr> <tr> <td colspan="2">Aging Condition (°Cxhrs)</td> <td colspan="2"></td> <td>100x168</td> <td></td> </tr> <tr> <td>After</td> <td>Tensile Strength (%)</td> <td colspan="2"></td> <td>&gt;=85% of unaged</td> <td></td> </tr> <tr> <td>Aging</td> <td>Elongation (%)</td> <td colspan="2"></td> <td>&gt;=50% of unaged</td> <td></td> </tr> <tr> <td colspan="4">Cold Bend(-20±2°Cx4hrs)</td> <td colspan="2">No crack</td> </tr> </tbody> </table>	Frequency (MHZ)	Attenuation Max(dB/100ft)	Attenuation Max(dB/100m)	SRL (dB)		5	0.79	2.57	5~1000MHz	>=20	10	0.82	2.66	50	1.47	4.79	100	2.05	6.72	200	2.84	9.28	400	4.06	13.28	700	5.6	18.36	1001~3000MHz	>=15	900	6.24	20.43	1000	6.6	21.61	1200	7.5	24.59	1450	8.04	26.36	1800	8.84	28.98	2200	9.77	32.03			2500	11.13	36.47			2750	11.58	37.94			3000	12.06	39.54						Dielectric Strength (kV/min)		1				Impedence (ohms)		75±3.0				Capacitance (pF/ft)		16.53				Conductor,DC@20 °C		31				DC Loop Resistance@ 20°C (ohms/kft)		45.45				Velocity Of Propagation (%)		85	Mechanical Characteristics:					Test Object				Jacket		Test Material				PVC		Before	Tensile strength (Mpa)			13.8		Aging	Elongation (%)			200		Aging Condition (°Cxhrs)				100x168		After	Tensile Strength (%)			>=85% of unaged		Aging	Elongation (%)			>=50% of unaged		Cold Bend(-20±2°Cx4hrs)				No crack	
DESCRIPTION																																																																																																																																																																																																							
RG6 Tri Shield, 18 AWG CCS, 60% Aluminum Braid, PVC Jacket, 1000ft Wooden Spool.																																																																																																																																																																																																							
Technical Data																																																																																																																																																																																																							
Operating Temperature Range(°C)	-20~75																																																																																																																																																																																																						
Reference Standard:	cETLus、CE、RoHS																																																																																																																																																																																																						
Construction																																																																																																																																																																																																							
<b>Conductor</b>																																																																																																																																																																																																							
Size	18AWG																																																																																																																																																																																																						
Material	Copper Clad Ateel(CCS)																																																																																																																																																																																																						
Construction	1.02±0.01mm																																																																																																																																																																																																						
<b>Dielectric</b>																																																																																																																																																																																																							
Material	Foam PE																																																																																																																																																																																																						
Diameter	4.75±0.01mm																																																																																																																																																																																																						
Color	White																																																																																																																																																																																																						
<b>First Shield</b>	Bonded Aluminum Foil																																																																																																																																																																																																						
<b>Braid</b>	Aluminum Wire(Alu-Mag )																																																																																																																																																																																																						
Coverage	60%x16x6x0.12±0.005mm																																																																																																																																																																																																						
<b>Third Shield</b>	Aluminum Foil																																																																																																																																																																																																						
<b>Jacket</b>																																																																																																																																																																																																							
Material	PVC																																																																																																																																																																																																						
Diameter	7.0±0.01mm																																																																																																																																																																																																						
Color	White																																																																																																																																																																																																						
Frequency (MHZ)	Attenuation Max(dB/100ft)	Attenuation Max(dB/100m)	SRL (dB)																																																																																																																																																																																																				
5	0.79	2.57	5~1000MHz	>=20																																																																																																																																																																																																			
10	0.82	2.66																																																																																																																																																																																																					
50	1.47	4.79																																																																																																																																																																																																					
100	2.05	6.72																																																																																																																																																																																																					
200	2.84	9.28																																																																																																																																																																																																					
400	4.06	13.28																																																																																																																																																																																																					
700	5.6	18.36	1001~3000MHz	>=15																																																																																																																																																																																																			
900	6.24	20.43																																																																																																																																																																																																					
1000	6.6	21.61																																																																																																																																																																																																					
1200	7.5	24.59																																																																																																																																																																																																					
1450	8.04	26.36																																																																																																																																																																																																					
1800	8.84	28.98																																																																																																																																																																																																					
2200	9.77	32.03																																																																																																																																																																																																					
2500	11.13	36.47																																																																																																																																																																																																					
2750	11.58	37.94																																																																																																																																																																																																					
3000	12.06	39.54																																																																																																																																																																																																					
			Dielectric Strength (kV/min)		1																																																																																																																																																																																																		
			Impedence (ohms)		75±3.0																																																																																																																																																																																																		
			Capacitance (pF/ft)		16.53																																																																																																																																																																																																		
			Conductor,DC@20 °C		31																																																																																																																																																																																																		
			DC Loop Resistance@ 20°C (ohms/kft)		45.45																																																																																																																																																																																																		
			Velocity Of Propagation (%)		85																																																																																																																																																																																																		
Mechanical Characteristics:																																																																																																																																																																																																							
Test Object				Jacket																																																																																																																																																																																																			
Test Material				PVC																																																																																																																																																																																																			
Before	Tensile strength (Mpa)			13.8																																																																																																																																																																																																			
Aging	Elongation (%)			200																																																																																																																																																																																																			
Aging Condition (°Cxhrs)				100x168																																																																																																																																																																																																			
After	Tensile Strength (%)			>=85% of unaged																																																																																																																																																																																																			
Aging	Elongation (%)			>=50% of unaged																																																																																																																																																																																																			
Cold Bend(-20±2°Cx4hrs)				No crack																																																																																																																																																																																																			